

DATE	REVISIONS	REV
10-24-95	CORRECTED EMITTER/COLLECTOR PIN NUMBERING./	A
12-22-97	E.C.N. #10BRDR./	B

DRAWING NUMBER OED-ST-23G	REV B
------------------------------	----------

ELECTRO-OPTICAL CHARACTERISTICS $T_A = 25^\circ\text{C}$


PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
COLLECTOR DARK CURRENT	I_{ceo}	$V_{ceo} = 10\text{V}$ $E_e = 0.5\text{mw/cm}^2$		1	100	nA
COLLECTOR LIGHT CURRENT	I_c	$V_{ce} = 5\text{V}$ $E_e = 0.5\text{mw/cm}^2$	0.5	4.0		mA
COLLECTOR-EMITTER SATURATION VOLTAGE	$V_{ce(sat)}$	$I_c = 0.2\text{mA}$ $E_e = 0.5\text{mw/cm}^2$		0.2	0.4	V
SWITCHING SPEEDS:						
RISING TIME	T_r	$V_{cc} = 5\text{V}$ $I_c = 1\text{mA}$		3.2		μS
FALLING TIME	T_f	$R_l = 100\Omega$		4.8		μS
PEAK WAVELENGTH	λ_p			880		nm
ANGULAR RESPONSE	$\Delta\theta$			± 30		DEG
LENS COLOR:	CLEAR					

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
COLLECTOR-EMITTER VOLTAGE (V_{ceo})	30	V
EMITTER-COLLECTOR VOLTAGE (V_{eco})	6	V
POWER DISSIPATION	100	mW
OPERATING TEMP.	-20 TO +100	$^\circ\text{C}$
STORAGE TEMP.	-30 TO +100	$^\circ\text{C}$
SOLDERING TEMP.	+260	$^\circ\text{C}$
2.0mm FROM BODY		3 SEC. MAX

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



UNLESS OTHERWISE SPECIFIED TOLERANCE IS $\pm 0.25\text{mm}$ (± 0.010)

LUMEX INCORPORATED		290 E. HELLEN ROAD PALATINE, ILLINOIS 60067 (847) 359-2790	
CONFIDENTIAL INFORMATION THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INCORPORATED. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INCORPORATED, THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.			
DATE:	12-22-97	DWN:	CHK'D:
SCALE:	N/A		APPD:
HIGH OUTPUT PHOTOTRANSISTOR, WATER CLEAR LENS, SIDE-EMITTING.			
PAGE 1 OF 1	DRAWING NUMBER OED-ST-23G	REV B	